

樹脂タイプネジ〔2MPS,2.6MPS,3MPS,4MPSシリーズ〕〔PPS〕1パック100本入)

- 樹脂タイプのネジです。耐熱性にすぐれた材質です。
- 絶縁が必要な場合に御利用下さい。
- 材質.....PPS樹脂 (UL94V-0)
- ねじり切断トルクネジ.....M2.....0.8kgf-cm (7.8N-cm)
 M2.6... 1.9kgf-cm (18.6N-cm)
 M3.....3kgf-cm (29.4N-cm)
 M4.....7kgf-cm (68.6N-cm)




- ナット.....M2.....0.8kgf-cm (7.8N-cm)
 M2.6... 1.9kgf-cm (18.6N-cm)
 M3.....3kgf-cm (29.4N-cm)
 M4.....7kgf-cm (68.6N-cm)

(参考値です。)(推奨締付けトルクは上記の50%で御使用下さい。)


- 使用温度範囲..... - 40 ~ + 200

2MPSシリーズ(M2用)




品番	L (mm)
2MPS- 4	4
2MPS- 5	5
2MPS- 6	6
2MPS- 8	8
2MPS-10	10
2MPS-12	12

2.6MPSシリーズ(M2.6用)




品番	L (mm)
2.6MPS- 6	6
2.6MPS- 8	8
2.6MPS-10	10
2.6MPS-12	12

3MPSシリーズ(M3用)




品番	L (mm)
3MPS- 5	5
3MPS- 6	6
3MPS- 8	8
3MPS-10	10
3MPS-12	12
3MPS-16	16
3MPS-20	20

4MPSシリーズ(M4用)



品番	L (mm)
4MPS- 6	6
4MPS- 8	8
4MPS-10	10
4MPS-12	12
4MPS-16	16
4MPS-20	20
4MPS-25	25

ナット



品番	A	B	C
3MPS-N	5.5	2.4	M3
4MPS-N	7	3.2	M4

樹脂ネジ